



Aquaflex®, an outstanding all-terrain UV resistant irrigation hose that delivers exceptional durability, flexibility and water flow performance.

Manufactured in the UK, Aquaflex® kink resistant water hose is the ideal heavy-duty choice for all irrigation purposes, as well as for water supply and delivery applications.

The multi-layered construction of Aquaflex®, using custom formulated materials and our exclusive high tensile braiding reinforcement technology, delivers superior flexibility and resilience in all weather conditions, ensuring performance levels that exceed those of comparable products in the professional hose market.

Key Features

- UV resistant.
- Highly flexible – ease of handling.
- Abrasion and kink resistance.
- Ultra smooth liner ensuring water flow performance.
- Resistant to repeated pulling, bending, crushing.
- Available in 25m, 50m and 100m coils.
- RoHS 3 compliant.

Sizes

Available in 25m, 50m and 100m coils

Applications

- Horticulture
- Fruit, vegetable growers
- Golf clubs
- Agriculture
- Landscaping
- Industrial
- Construction
- Public sector



"We recently trialed Aquaflex from Fargro as an alternative to our existing hosepipe brand on the nursery. With recent price increases we were looking for something that performed well without a prohibitive price tag.

The Aquaflex was put through its paces throughout the nursery, dragged between the benches, stretched around corners, pulled, driven over and left standing in the last of the winter frosts. The hose performed well at every level, kink free, split free and delivering water to where we need it."



NURSERY MANAGER
FERRING NURSERIES



1. High strength Phthalate free PVC
2. Polyester fiber reinforcement
3. UV resistant PVC cover

Aquaflex Irrigation Hose

F/CODE	DESCRIPTION	INTERNAL DIAMETER	EXTERNAL DIAMETER	WALL THICKNESS	MINIMUM WORKING PRESSURE	MINIMUM BURST PRSSURE	WEIGHT PER METRE	BEND RADIUS
AQFH12A	12.5mm x 25m	12.5mm	17.5mm	2.5mm	16 Bar	48 Bar	0.158kg	100mm
AQFH12B	12.5mm x 50m	12.5mm	17.5mm	2.5mm	16 Bar	48 Bar	0.158kg	100mm
AQFH12C	12.5mm x 100m	12.5mm	17.5mm	2.5mm	16 Bar	48 Bar	0.158kg	100mm
AQFH19A	19mm x 25m	19mm	25.5mm	3.25mm	13 Bar	39 Bar	0.313 kg	120mm
AQFH19B	19mm x 50m	19mm	25.5mm	3.25mm	13 Bar	39 Bar	0.313 kg	120mm
AQFH19C	19mm x 100m	19mm	25.5mm	3.25mm	13 Bar	39 Bar	0.313 kg	120mm
AQFH25A	25mm x 25m	25mm	32.5mm	3.75mm	8 Bar	39 Bar	0.465 kg	200mm
AQFH25B	25mm x 50m	25mm	32.5mm	3.75mm	8 Bar	39 Bar	0.465 kg	200mm
AQFH25C	25mm x 100m	25mm	32.5mm	3.75mm	8 Bar	39 Bar	0.465 kg	200mm